

BRIGHTO STUCCO FILLER

General Description	Brighto Stucco Filler is a good quality water based filler. It smoothens the surface for application of Brighto topcoats. It has good filling and sanding properties. It is formaldehyde and lead free.
Pack Size	3.60 Liters, 18 Liters
Colour Range	White / Natural
Film Properties Water Resistance	Will tolerate to the levels of atmospheric humidity present in normal environment.
Composition (Nominal)	Pigment: Lightfast Pigments Binder: Acrylic Copolymer Solvent: Water
Volume Solids	51 ± 2% (nominal)
Density	1.65 ± 0.03; Theoretical
Non-volatile Matter Content	70 ± 2; Theoretical
VOC Contents	4.9 g/L ; ISO 11890-1
Film Thickness/Coat	Wet: 100 - 150 Micrometers Dry: 50 - 75 Micrometers
Drying Times	Depends on temperature, humidity, air movements and film thickness
Touch Dry	1 Hour
Recoat	2 - 4 Hours
Hard Dry	24 hours
Theoretical Coverage	A guide to the theoretical coverage which can be achieved under normal conditions is 7 - 10 m ² /liter /coat.
Application	Putty knife, Scrapper
Thinner	Water
Dilution	Maximum 5% (If Required)
Conventional Spray	Not applicable
Cleaning Up	Clean all equipment with clean water immediately after use.

Surface Preparation

New, bare, old or previously painted surfaces must be clean, dry and free from dust or wax. Clean the surface by rubbing down with abrasive paper. Brush down previously painted surface completely and make the surface smooth. Dust off with the help of cloth, use recommended application procedure for application. Stir the paint thoroughly before use.

Recommended Paint System

Brighto PVA / Acrylic Primer	1 Coat
Brighto Stucco Filler	2 Coats

Safety, Health and Environmental Information

Keep container tightly closed and upright to prevent leakage when not in use. Don't breathe in vapors and sanding dust. Cartridge mask should be worn when rubbing down. Provide adequate ventilation during application and drying. If you experience difficulty in breathing, move to fresh air. Don't permit smoking in the vicinity. Avoid contacts with eyes and skin. Wear gloves and goggles during application or sanding. In case of contact with eyes, flush with plenty of water and seek medical advice. To remove splashes from skin, use soap and water or recognized skin cleaner. Protect from extremes of temperatures. Store in a cool dry place but also protect from freezing. In case of fire, use foam, dry powder, CO2 fire extinguisher. Keep away from source of ignition. Close container tightly after each use. Keep out of reach of children. In case of accident, collect spillage using sand or clay and dispose of paint waste in accordance with appropriate environmental quality requirements.

Any advice recommendations, information, assistance or service provided by Brighto Paints Pvt. Ltd. in relation to goods manufactured or marketed by it or their use or any applications is given in good faith without expressed or implied warranties.